



# DOUBLE CRANK CROSS SHAFT POWER PRESS

W: [mankoopresses.com](http://mankoopresses.com)  
E: [mankooindia@gmail.com](mailto:mankooindia@gmail.com)  
[info@mankoopresses.com](mailto:info@mankoopresses.com)  
P: (O) +91-161-2510948, 5022948, 9988802100

**Mankoo India Pvt. Ltd**  
29 / 535, G.T. Road,  
Opp. Dhandari Kalan Railway Station,  
Ludhiana - 141010. Punjab. INDIA.

## Description

Double Crank Cross Shaft C Frame Power Presses are applicable for single and progressive die application in blanking, piercing, bending, forming. You can interlink them with transfer unit. These presses are having Rigid frame with less deflection & Wide bolster and side area. These presses are most suitable for automobile components & white good industry

SPECIFICATION		MINX-2-110	MINX-2-160	MINX-2-200	MINX-2-250	MINX-2-300
Capacity	Ton	110	160	200	250	300
Length of Stroke	mm	180	200	230	250	280
Stroke Per Minute	S.P.M	50	40	35	30	30
Tonnage Rating Point at B. D. C	mm	5	6	7	7	8
Die Height	mm	400	450	500	550	550
Adjustment of Slide	mm	90	100	110	120	120
Area of Slide	mm	1430×520	1560×580	1850×650	2100×700	2100×800
Diameter of Shank Hole	mm	51	51	51	51	51
Area of Bolster	mm	1880×680	2040×760	2420×840	2700×920	2700×900
Thickness of Bolster	mm	150	160	170	180	200
Throat Depth	mm	900	950	1000	1100	1100
Main Motor	Hp x p	10HP x 4P	15Hp x 4P	20Hp x 4P	25Hp x 6P	30Hp x 4P
Foot Size	mm	1980 × 1760	2170 × 2030	2520 × 2165	2810 × 2470	2870 × 2535
Floor Space Required	mm	2090 × 1760	2275 × 2030	2650 × 2165	2915 × 2470	2945 x2535
Overall Height	mm	3098	3378	3370	4138	4368
Die Cushion (Optional)						
Capacity (at 5kg /cm <sup>2</sup> )	tf	6 × 2	8 × 2	10 × 2	14 × 2	14 × 2
Length of stroke	mm	70	90	100	120	120
Area of Pads (R.L X F.B)	mm	480 × 340 x2	560 × 370 × 2	700 × 450 × 2	700 × 450 × 2	700 × 450 × 2

