

STRAIGHT SIDE DOUBLE CRANK POWER PRESS



W: mankoopresses.com
E: mankooindia@gmail.com
info@mankoopresses.com
P: (O) +91-161-2510948, 5022948, 9988802100

Mankoo India Pvt. Ltd
29 / 535, G.T. Road,
Opp. Dhandari Kalan Railway Station,
Ludhiana - 141010. Punjab. INDIA.

Description

MIXP – 2 SERIES TWO POINT H FRAME CROSS SHAFT POWER PRESS is having and Box Type Steel Welded Construction with Minimum Frame Deflection. The Slide Moves In 4 Point Long Guides & Motorized Slide Adjustment With Die Height Indicator (0.1 MM). It is equipped with a Dual Solenoid Valve For Safety

Specifications For Straight Side Double Crank Power Press

SPECIFICATION

Straight Side Double Crank Power Press

| Model | | MIXP-2-160 | MIXP-2-200 | MIXP-2-250 | MIXP-2-315 | MIXP-2-400 | MIXP-2-500 |
|----------------------|-------|------------|------------|------------|------------|------------|------------|
| Capacity | Tonne | 160 | 200 | 250 | 315 | 400 | 500 |
| Fix Stroke | mm | 200 | 220 | 250 | 300 | 300 | 300 |
| SPM | spm | 40 | 35 | 30 | 30 | 25 | 20 |
| Tonnage Rating point | mm | 6 | 7 | 7 | 7 | 7 | 9 |
| Die Height | mm | 450 | 500 | 550 | 550 | 600 | 650 |
| Slide Adjustment | mm | 10 | 100 | 120 | 120 | 150 | 175 |
| Slide Area | mm | 1560×650 | 1850×750 | 2100×820 | 2100×900 | 2200×1000 | 2200×1000 |
| Bolster Area | mm | 1850x 760 | 2200×840 | 2500×920 | 2500×1100 | 2500×1100 | 2500×1100 |
| Bolster Thickness | mm | 160 | 170 | 180 | 200 | 200 | 220 |
| Main Motor | hp/px | 15×4 | 20×4 | 25×4 | 30×4 | 40×4 | 50×4 |
| Slide Adjustment | kw | 0.75 | 1.5 | 1.5 | 1.5 | 2.2 | 2.2 |
| Die Cushion | | | | | | | |
| Type | | Bellow | Bellow | Bellow | Bellow | Bellow | Bellow |
| Capacity | Tonne | 8×2-16T | 10×2-20T | 14×2-28T | 14×2-28T | 20×2-40T | 20×2-40T |
| Stroke Length | mm | 110 | 130 | 140 | 140 | 150 | 150 |
| Pad Area | mm | 560×370×2 | 700×450×2 | 700×540×2 | 700×540×2 | 900×600×2 | 900×600×2 |

