



# STRAIGHT SIDE SINGLE CRANK POWER PRESS

W: [mankoopresses.com](http://mankoopresses.com)  
E: [mankooindia@gmail.com](mailto:mankooindia@gmail.com)  
[info@mankoopresses.com](mailto:info@mankoopresses.com)  
P: (O) +91-161-2510948, 5022948, 9988802100

**Mankoo India Pvt. Ltd**  
29 / 535, G.T. Road,  
Opp. Dhandari Kalan Railway Station,  
Ludhiana - 141010. Punjab. INDIA.

## Description

MIXH – 1 SERIES Straight Side Single Crank Power Pressis having and Box Type Steel Welded Construction with Minimum Frame Deflection. The Slide Moves In 4 Point Long Guides & Motorised Slide Adjustment With Die Height Indicator (0.1 MM). It is equipped with a Dual Solenoid Valve For Safety

## Specifications

### For **Straight Side Single Crank Power Press**

SPECIFICATION					
Model		MXH1-110	MXH1-160	MXH1-200	MXH1-250
Capacity		110	160	200	250
Stroke Length	mm	125	160	200	220
Stroke Length Variable	mm	8-25	8-160	-	-
Stroke Per Min	SPM	50	40	35	30
Rated Tonnage Point	mm	5	6	6	6
Shut Height	mm	360	450	500	500
Slide Adjustment	mm	90	100	120	120
Slide Area (PxQ)	mm	650×520	720×580	800×680	900×800
Bolster Area (LR x FB)	mm	1000×680	1100×760	1250×840	1300×900
Bolster Thickness	mm	140	165	180	180
Floor To Bolster	mm	900	900	1000	1000
Window in upright	mm	650×350	700×400	800×450	800×450
Main Motor	HP	10	15	20	25
Motor of Slide Adjustment	HPxP	1×4	2×4	2×4	2×4
Overall Space	mm	1600×1830	1750×2135	1970×2250	2020×2540
Press Height(w/o mounts)	mm	2950	3235	3685	3775
Air Pressure Required	Kg/cm	5	5	5	5
Pneumatic Die Cushion	Tonnage	10	15	20	25
Stroke	mm	70	90	110	110
(Optional)	Pad Area	480×300	540×340	640×440	640×440

W: [mankoopresses.com](http://mankoopresses.com)

E: [mankooindia@gmail.com](mailto:mankooindia@gmail.com)

[info@mankoopresses.com](mailto:info@mankoopresses.com)

P: (O) +91-161-2510948, 5022948, 9988802100

**Mankoo India Pvt. Ltd**

29 / 535, G.T. Road,

Opp. Dhandari Kalan Railway Station,

Ludhiana – 141010. Punjab. INDIA.

