



Two Point H Frame UNGEARED HIGH SPEED PRESS

W: mankoopresses.com
E: mankooindia@gmail.com
info@mankoopresses.com
P: (O) +91-161-2510948, 5022948, 9988802100

Mankoo India Pvt. Ltd
29 / 535, G.T. Road,
Opp. Dhandari Kalan Railway Station,
Ludhiana - 141010. Punjab. INDIA.

Description

TWO POINT H FRAME UNGEARED HIGH SPEED PRESSES are heavy duty presses used for bigger dies. It is suitable for MOTOR LAMINATION and progressive dies. They are equipped with Motorized Ram adjustment. The Main frame of the press is of all welded to up right straight line type constructed of thick rolled plates. Available

Specifications

Two Point H Frame Ung geared High Speed Press

SPECIFICATION							
Model		MIHS-40	MIHS-63	MIHS-100	MIHS-160	MIHS-200	MIHS-315
Capacity	Tonne	40	63	100	160	200	315
Stroke Length	mm	25	25	30	30	30	40
Strokes Per Min.	spm	100-200	100-200	100-200	90-180	90-180	80-160
Die Height	mm	260	315	330	350	400	450
Slide Adjustment	mm	40	40	40	50	50	50
Slide Area (LR x FB)	mm	600x350	700x400	900x500	1150x630	1400x700	1700x800
Bolster Area (LR x FB)	mm	700x500	800x600	1050x800	1300x850	1500x900	1800x900
Bolster Thickness	mm	80	100	130	160	175	200
Bed Opening (LR X FB)	mm	500x200	600x225	850x250	1100x300	1300x350	1500x380
Slide Opening (F-B) x HT in column	mm	225x200	250x200	280x250	315x275	380x300	450x300
Main Motor	kw	7.5	7.5	11	15	22	37
Air Pressure Atm	kg/cm ²	5.5	5.5	5.5	5.5	5.5	5.5

